

Pipe poles are ideal for use in sporting applications, commercial and industrial projects.

Pipe poles are made from circular pipe and square mild steel sections and are available in a range of heights up to 12m. Access doors are included.

The mounting options are in-ground mount, base plate for foundation bolts or base plate for Ezi-Fit in-ground base section.

Options List

- Post Top (standard)
- Single Outreach.
- Double Outreach.
- Ezi-Fit in-ground base section.
- In-ground mount.
- Base plate mount.
- Spigot to suit various types of light fittings.

Standard finish Galvanized.

Commonly used colours.



Extensive range of colours available. For coastal environments a coastal paint specification is available on request.

Circular Section Pipe Poles

Height	Pole OD	Mounting
3.0m	76mm, 90mm or 102mm	M16 Rag Bolt Inground 1m
3.5m	76mm, 90mm or 102mm	M16 Rag Bolt Inground 1.25m
4.0m	90mm, 102mm or 114mm	M16 Rag Bolt Inground 1.25m
4.5m	90mm, 102mm or 114mm	M16 Rag Bolt Inground 1.25m
5.0m	90mm, 102mm or 114mm	M20 Rag Bolt Inground 1.5m
6.0m	90mm, 102mm or 114mm	M20 Rag Bolt Inground 1.5m
8.0m	114mm or 141mm	M20 Rag Bolt Inground 1.5m
10.0m	141mm or 168mm	M24 Rag Bolt Inground 1.8m
12.0m	168mm or 220mm	M24 Rag Bolt Inground 2m

Note: other sizes and heights (12m maximum) available on request

Square Section Pipe Poles

Height	Square Section Size	Mounting
3.0m	75mm, 89mm or 100mm	M16 Rag Bolt Inground 1m
3.5m	75mm, 89mm or 100mm	M16 Rag Bolt Inground 1.25m
4.0m	89mm or 100mm	M16 Rag Bolt Inground 1.25m
4.5m	89mm or 100mm	M16 Rag Bolt Inground 1.25m
5.0m	89mm or 100mm	M20 Rag Bolt Inground 1.5m
6.0m	100mm or 125mm	M20 Rag Bolt Inground 1.5
7.0m	100mm or 125mm	M20 Rag Bolt Inground 1.5m
8.0m	100mm or 125mm	M20 Rag Bolt Inground 1.5m
9.0m	125mm	M24 Rag Bolt Inground 1.8m

Note: other sizes and heights (12m maximum) available on request